

Date tehnice pentru produs: BK080008--

Dulap distrib. încastr. 1 rânduri, 24UH, ușă transp.

Î=254mm, L=498mm, A=106mm, IP40, ABS, halogen free, RAL 9003, clasa de protecție 2



SCHRACK-Info

- Flush-mounted domestic consumer unit enclosures in ABS with transparent plastic doors
- Lock: push-button, a small cylinder can be installed
- Includes PE and N terminals
- Protection class II
- Halogen free according to RoHS
- Rated voltage 400VAC / In=63A
- Ambient temperature: -25° to +60°C
- Glow wire test: 650°C
- Recess depth: 68-70mm
- Degree of protection: IP40, Impact resistance: IK08
- RAL9010 pure white



Fișe tehnice

Lățime netă (mm)

498,00

Fișe tehnice - Continuare

Înălțime (mm)	254,00
Adâncime netă (mm)	106,00
Masă netă (kg.)	1,44
COD EAN	9004840917017
disipare (W)	-30,00
Temperatura minimă a mediului ambiant (°C)	-25
Temperatura maximă a mediului ambiant (°C)	60
Material ușă	plastic transparent
Fără halogen	Yes
Versiune	îngropat cu ușă
Rânduri	1
module / rând	24
grad de protecție	IP40
Culoare	RAL 9003 (alb)

Tabel articole

Descriere	Cod comandă
Dulap distrib. încastr. 1 rânduri, 24UH, ușă transp. Î=254mm, L=498mm, A=106mm, IP40, ABS, halogen free, RAL 9003, clasa de protecție 2	BK080008
Accesorii opționale	
Încuietoare cilindru metalic pentru BK08... IP40	BK080096