

Date tehnice pentru produs: BK090206--

Dulap distrib. apl. IP65, 54UH, 3 rând. cu ușa transparentă

Rezistent la UV și la stările atmosferice, 1000Vcc, ABS, 3x18UH, Î=638mm, L=432mm, A=160mm, 2 x N+PE(22x16mm²)



SCHRACK-Info

- Wall-mounted enclosures with one transparent door inclusive UV-Protection
- Lock: Pressure-operated mechanism, a small cylinder can be installed
- Cable Entry by elastic rubber membranes
- Includes PE and N terminals
- Halogen-free plastic materials
- Protection class II
- UV stability and weather resistant

- Rated voltage 400VAC, 1000VDC
- Ambient temperature: -25° to +85°C
- Material: ABS
- Degree of protection IP65
- Resistance to impact: IK07
- RAL7035 light grey

Fișe tehnice

Lățime netă (mm)	432,00
Înălțime (mm)	638,00
Adâncime netă (mm)	160,00
Masă netă (kg.)	5,72
COD EAN	9004840817959
disipare (W)	-35,00
Temperatura minimă a mediului ambiant (°C)	-25
Temperatura maximă a mediului ambiant (°C)	85

Tabel articole

Descriere	Cod comandă
Dulap distrib. apl. IP65, 54UH, 3 rând. cu ușă transparentă Rezistent la UV și la stările atmosferice, 1000Vcc, ABS, 3x18UH, Î=638mm, L=432mm, A=160mm, 2 x N+PE(22x16mm ²)	BK090206
Accesorii opționale	
Incuietoare pentru cofrete BK09 IP65	BK090097