

Date tehnice pentru produs: HSATWT50S-

Set 50 cm. suporți montaj SAT, oțel galvanizat la cald

hot-galvanized, two-part



SCHRACK-Info

Hot-dip galvanized steel wall bracket, 2-part, for the securely attaching a mast tube with a diameter of Ø 38 to 60mm to the wall. Wall distance: 150mm, adjustable by 10cm. Mast tube not included.

TECHNICAL DATA

- Material: Quality steel
- Struts : Flat profile 30 x 5mm
- Surface: hot-dip galvanizing approx. 80
- Wall distance: 500mm, adjustable up to 10cm
- twist-proof: with 2x twist-proof claws
- consisting of: 1x bipod and 1x tripod holder
- suitable for mast tubes : Ø 38 to 60mm

Fișe tehnice

Lungime (mm)	520,00
Lățime netă (mm)	560,00
Înălțime (mm)	50,00
Masă netă (kg.)	3,90
Temperatura minimă a mediului ambiant (°C)	-40
Temperatura maximă a mediului ambiant (°C)	60

Tabel articole

Descriere	Cod comandă
Set 50 cm. suportți montaj SAT, oțel galvanizat la cald hot-galvanized, two-part	HSATWT50S
Accesorii opționale	
Extensie catarg L=2000mm,D50mm,OI Zn de 1.5mm grosime	HSATMM20S
Catarg L=2000mm,D60mm,include capac capăt, Oțel galvanizat 2	HSATMM20S6
Extensie catarg L=3000mm,D50mm,OI Zn de 2mm grosime	HSATMM30S
Catarg L=3000mm,D60mm,include capac capăt, Oțel galvanizat 2	HSATMM30S6