

Date tehnice pentru produs: HVSMRJ5UWS

Jack RJ45 neecranat, Cat.5e (SFA)



SCHRACK-Info

TRANSMISSION PERFORMANCE

- Meet all requirements specified in connecting hardware requirement of ANSI/TIA-568-C.2, Category 5e

ELECTRICAL

- Electrical Insulation Resistance: 500MΩ min. 100VDC
- Dielectric Withstanding Voltage : 1000VDC or a.c. Peak Contact to Contact 60Hz for 1 minute

MECHANICAL

- Insertion / Extraction Life: 750 Cycles Minimum
- IDC Wire Gauge: 22 ~ 24 AWG

PHYSICAL

- Housing: High-Impact, Flame-Retardant Plastic, UL 94V-0
- Spring Wire: Phosphor Bronze Alloy Plated with 50μ-inch of Gold
- IDC: Phosphor Bronze Alloy with 100μ-inch 100% Sn Alloy



Fișe tehnice

Lățime netă (mm)	16,90
Înălțime (mm)	21,90

Fișe tehnice - Continuare

Temperatura minimă a mediului ambiant (°C)	-10
Temperatura maximă a mediului ambiant (°C)	60

Tabel articole

Descriere	NVP (%)	Greutate cupru (kg/km)	Cod comandă
Jack RJ45 neecranat, Cat.5e (SFA)			HVSMRJ5UWS
Accesorii opționale			
Clește sertizat HVSMRJ5UWS / HVSMRJ6UWS			HVSTOOL01S
Cablu U/UTP Cat.5e, 4x2xAWG24/1, PVC, Eca, albastru, cutie	69	15	HSEKU424P1
Cablu U/UTP Cat.5e, 4x2xAWG24/1, PVC, Eca, gri, cutie	69	15	HSEKU424P0
Cablu U/UTP Cat.5e, 4x2xAWG24/1, LSOH, Eca, albastru, cutie	69	15	HSEKU424H1
Patchpanel pt. 24 module TOOLLESS LINE, 1 UH, 19", RAL7035			HSER0240GS
Patchpanel TOOLLESS LINE, neechipat, 1 modul, montaj pe șină			HSERH010GS
Priză pt. 1 modul TOOLLESS LINE, 80x80mm, înclinat, RAL9010			HSED01UW2S
Priză pt. 2 module TOOLLESS LINE, 80x80mm, înclinat, RAL9010			HSED02UW2S