

Date tehnice pentru produs: IG009401--

## Cable management enclosure Series J, dotted, 1 door, size 00

H=1100 W=471 D=320mm, door opening angle 180°



### SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

#### Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



### Fișe tehnice

|                  |          |
|------------------|----------|
| Lățime netă (mm) | 471,00   |
| Înălțime (mm)    | 1.100,00 |

## Fișe tehnice - Continuare

|                      |                                          |
|----------------------|------------------------------------------|
| Adâncime netă (mm)   | 320,00                                   |
| Masă netă (kg.)      | 22,57                                    |
| COD EAN              | 4029155649922                            |
| disipare (W)         | -217,71                                  |
| Material             | Polyester Glass Fibre Reinforced Plastic |
| Categorie produs     | Cable Management Enclosure               |
| Înălțime (mm)        | 1100                                     |
| Lățime (mm)          | 440                                      |
| Adâncime (mm)        | 320                                      |
| Număr de uși         | 1                                        |
| Tip ușă              | cu o ușă striată                         |
| Încuietoare          | Swinghandle, prepared for Half cylinder  |
| Culoare              | RAL 7035 (Gri deschis)                   |
| grad de protecție    | IP44                                     |
| Clasă de protecție   | II                                       |
| Rezistentă la impact | IK10                                     |

## Tabel articole

| Descriere                                                                                                                         | Greutate cupru (kg/km) | Cod comandă |
|-----------------------------------------------------------------------------------------------------------------------------------|------------------------|-------------|
| Cable management enclosure Series J, dotted, 1 door, size 00<br>H=1100 W=471 D=320mm, door opening angle 180°                     |                        | IG009401    |
| <b>Accesorii opționale</b>                                                                                                        |                        |             |
| Mountingplate for IG009401, H=985 W=375 D=5mm<br>including fastening screws, mounting plate made of melamine-laminated hard paper |                        | IG009441    |
| plastic base frame sizes 00/S3 and 0/S4 600/400<br>plastic base frame serving as a foundation for plinth                          |                        | IG790328    |
| base filler - hydrophobic<br>100 liter bag, water-repellent - hydrophobic                                                         |                        | IG790333    |
| base filler expanded clay 4-8mm round 50L<br>water-absorbing - expanded clay, 50 liter bag                                        |                        | IG790570    |
| foam insert size 00/S3/310 (absorption mat)                                                                                       |                        | IG793816    |
| Plinth Polyester Series J size 00, RAL7035<br>H=902 W=450 D=310mm                                                                 |                        | IG009311    |
| Adapter bar for KVS - IG009401, size 00 (PU= 2 pcs.)<br>Pre-cut with M6 machine tap bit                                           |                        | IG009461    |

## Tabel articole

| Descriere                                                                                                                        | Greutate cupru (kg/km) | Cod comandă |
|----------------------------------------------------------------------------------------------------------------------------------|------------------------|-------------|
| <b>Accesorii opționale</b>                                                                                                       |                        |             |
| Modular chassis 1-21K, 7-rows, complete                                                                                          |                        | IL148121-A  |
| Front plates sheet steel                                                                                                         |                        |             |
| self-cutting Lens Head Screw M6 (PU = 4Pieces)                                                                                   |                        | IG009000    |
| for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--                                                 |                        |             |
| Wall mounting kit Size 00-2, for IG0094 und IG0095                                                                               |                        | IG009500    |
| Ground plate for Wall mounting for IG009401 & IG009501                                                                           |                        | IG009421    |
| H=288 W=429 D=4mm                                                                                                                |                        |             |
| Copper busbar Set 4-pole, 30x10mm for Size 00                                                                                    |                        |             |
| For IG009401 and IG009501, 4 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers | 3400                   | IG00903100  |
| Copper busbar, 30x10mm for Size 00                                                                                               |                        |             |
| For IG009401 and IG009501, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers                                    | 1120                   | IG009P3100  |
| Obturator de 100 mm pentru sistem de bară de 185 mm                                                                              |                        | ISA05360    |
| Se montează pe piulițele prelungite M12                                                                                          |                        |             |
| Insert (butuc) semi-cilindric cu 3 chei H36000, L=40 mm                                                                          |                        | IL900381    |