

Date tehnice pentru produs: IG009402--

Cable management enclosure Series J, dotted, 1 door, size 0

H=1100 W=605 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Fișe tehnice

Lățime netă (mm)	605,00
Înălțime (mm)	1.100,00

Fișe tehnice - Continuare

Adâncime netă (mm)	320,00
Masă netă (kg.)	25,25
COD EAN	4029155144885
disipare (W)	-257,56
Material	Polyester Glass Fibre Reinforced Plastic
Categorie produs	Cable Management Enclosure
Înălțime (mm)	1100
Lățime (mm)	590
Adâncime (mm)	320
Număr de uși	1
Tip ușă	cu o ușă striată
Încuietoare	Swinghandle, prepared for Half cylinder
Culoare	RAL 7035 (Gri deschis)
grad de protecție	IP44
Clasă de protecție	II
Rezistentă la impact	IK10

Tabel articole

Descriere	Greutate cupru (kg/km)	Cod comandă
Cable management enclosure Series J, dotted, 1 door, size 0 H=1100 W=605 D=320mm, door opening angle 180°		IG009402
Accesorii opționale		
Mountingplate for IG009402, H=985 W=500 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009442
plastic base frame sizes 00/S3 and 0/S4 600/400 plastic base frame serving as a foundation for plinth		IG790328
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 0/S4/310 (absorption mat)		IG793818
Plinth Polyester Series J size 0, RAL7035 H=902 W=585 D=310mm		IG009312
Adapter bar for KVS - IG009402, size 0 (PU= 2 pcs.) Pre-cut with M6 machine tap bit		IG009462

Tabel articole

Descriere	Greutate cupru (kg/km)	Cod comandă
Accesorii opționale		
Modular chassis 2-21K, 7-rows, complete		IL148221-A
Front plates sheet steel		
self-cutting Lens Head Screw M6 (PU = 4Pieces)		IG009000
for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--		
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009402 & IG009502		IG009422
H=288 W=563 D=4mm		
Copper busbar Set 4-pole, 30x10mm for Size 0		
For IG009402 and IG009502, 5 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	4550	IG0090310
Copper busbar, 30x10mm for Size 0		
For IG009402 and IG009502, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	1440	IG009P310
Copper busbar Set 4-pole, 40x10mm for Size 0		
For IG009402 and IG009502, 5 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	6160	IG0090410
Obturator de 100 mm pentru sistem de bară de 185 mm		ISA05360
Se montează pe piulițele prelungite M12		
Insert (butuc) semi-cilindric cu 3 chei H36000, L=40 mm		IL900381