

Date tehnice pentru produs: IG009403--

Cable management enclosure Series J, dotted, 1 door, size 1

H=1100 W=800 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Fișe tehnice

Lățime netă (mm)	800,00
Înălțime (mm)	1.100,00

Fișe tehnice - Continuare

Adâncime netă (mm)	320,00
Masă netă (kg.)	29,86
COD EAN	4029155575313
disipare (W)	-315,56
Material	Polyester Glass Fibre Reinforced Plastic
Categorie produs	Cable Management Enclosure
Înălțime (mm)	1100
Lățime (mm)	785
Adâncime (mm)	320
Număr de uși	1
Tip ușă	cu o ușă striată
Încuietoare	Swinghandle, prepared for Half cylinder
Culoare	RAL 7035 (Gri deschis)
grad de protecție	IP44
Clasă de protecție	II
Rezistentă la impact	IK10

Tabel articole

Descriere	Greutate cupru (kg/km)	Cod comandă
Cable management enclosure Series J, dotted, 1 door, size 1 H=1100 W=800 D=320mm, door opening angle 180°		IG009403
Accesorii opționale		
Mountingplate for IG009303, H=985 W=680 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009443
plastic base frame sizes 1/S5 800/400		IG790329
plastic base frame serving as a foundation for plinth		
base filler - hydrophobic		IG790333
100 liter bag, water-repellent - hydrophobic		
base filler expanded clay 4-8mm round 50L		IG790570
water-absorbing - expanded clay, 50 liter bag		
foam insert size 1/S5/310 (absorption mat)		IG793819
Plinth Polyester Series J size 1, RAL7035		IG009313
H=902 W=780 D=310mm		
Adapter bar for KVS - IG009403, size 1 (PU= 2 pcs.)		IG009463
Pre-cut with M6 machine tap bit		

Tabel articole

Descriere	Greutate cupru (kg/km)	Cod comandă
Accesorii opționale		
Modular chassis 3-21K, 7-rows, complete		IL148321-A
Front plates sheet steel		
self-cutting Lens Head Screw M6 (PU = 4Pieces)		IG009000
for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--		
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009403 & IG009503		IG009423
H=288 W=758 D=4mm		
Copper busbar Set 4-pole, 30x10mm for Size 1		
For IG009403 and IG009503, 7 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	6520	IG0090311
Copper busbar, 30x10mm for Size 1		
For IG009403 and IG009503, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	1980	IG009P311
Copper busbar, 40x10mm for Size 1		
For IG009403 and IG009503, 7 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	8840	IG0090411
Obturator de 100 mm pentru sistem de bară de 185 mm		ISA05360
Se montează pe piulițele prelungite M12		
Insert (butuc) semi-cilindric cu 3 chei H36000, L=40 mm		IL900381