

Date tehnice pentru produs: IG009501--

# Cable management enclosure Series J, 1 door, size 00

dotted surface, H=850 W=471 D=320mm, door opening angle 180°



## SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

### Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



## Fișe tehnice

|                  |        |
|------------------|--------|
| Lățime netă (mm) | 471,00 |
| Înălțime (mm)    | 850,00 |

## Fișe tehnice - Continuare

|                      |                                          |
|----------------------|------------------------------------------|
| Adâncime netă (mm)   | 320,00                                   |
| Masă netă (kg.)      | 18,18                                    |
| grad de protecție    | IP44                                     |
| Clasă de protecție   | II                                       |
| Rezistență la impact | IK10                                     |
| Material             | Polyester Glass Fibre Reinforced Plastic |
| Culoare              | RAL 7035 (Gri deschis)                   |
| Lățime (mm)          | 471                                      |
| Înălțime (mm)        | 850                                      |
| Adâncime (mm)        | 320                                      |
| Număr de uși         | 1                                        |
| Încuietoare          | Swinghandle, prepared for Half cylinder  |

## Tabel articole

| Descriere                                                                                                                         | Greutate cupru (kg/km) | Cod comandă |
|-----------------------------------------------------------------------------------------------------------------------------------|------------------------|-------------|
| Cable management enclosure Series J, 1 door, size 00<br>dotted surface, H=850 W=471 D=320mm, door opening angle 180°              |                        | IG009501    |
| <b>Accesorii opționale</b>                                                                                                        |                        |             |
| Mountingplate for IG009501, H=735 W=375 D=5mm<br>including fastening screws, mounting plate made of melamine-laminated hard paper |                        | IG009551    |
| plastic base frame sizes 00/S3 and 0/S4 600/400<br>plastic base frame serving as a foundation for plinth                          |                        | IG790328    |
| base filler - hydrophobic<br>100 liter bag, water-repellent - hydrophobic                                                         |                        | IG790333    |
| base filler expanded clay 4-8mm round 50L<br>water-absorbing - expanded clay, 50 liter bag                                        |                        | IG790570    |
| foam insert size 00/S3/310 (absorption mat)                                                                                       |                        | IG793816    |
| Plinth Polyester Series J size 00, RAL7035<br>H=902 W=450 D=310mm                                                                 |                        | IG009311    |
| Ground plate for Wall mounting for IG009301<br>H=285 W=425 D=4mm                                                                  |                        | IG009321    |
| Wall mounting kit Size 00-2, for IG0094 und IG0095                                                                                |                        | IG009500    |
| Ground plate for Wall mounting for IG009401 & IG009501<br>H=288 W=429 D=4mm                                                       |                        | IG009421    |

## Tabel articole

| Descriere                                                                                                                                                                         | Greutate cupru (kg/km) | Cod comandă |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-------------|
| <b>Accesorii opționale</b>                                                                                                                                                        |                        |             |
| Copper busbar Set 4-pole, 30x10mm for Size 00<br>For IG009401 and IG009501, 4 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers | 3400                   | IG00903100  |
| Copper busbar, 30x10mm for Size 00<br>For IG009401 and IG009501, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers                                               | 1120                   | IG009P3100  |
| Obturator de 100 mm pentru sistem de bară de 185 mm<br>Se montează pe piulițele prelungite M12                                                                                    |                        | ISA05360    |
| Insert (butuc) semi-cilindric cu 3 chei H36000, L=40 mm                                                                                                                           |                        | IL900381    |