

Date tehnice pentru produs: IG009505--

Cable management enclosure Series J, 2 doors, size 2

dotted surface, H=850 W=1130 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Fișe tehnice

Lățime netă (mm)	1.130,00
Înălțime (mm)	850,00

Fișe tehnice - Continuare

Adâncime netă (mm)	320,00
Masă netă (kg.)	33,38
grad de protecție	IP44
Clasă de protecție	II
Rezistentă la impact	IK10
Material	Polyester Glass Fibre Reinforced Plastic
Culoare	RAL 7035 (Gri deschis)
Lățime (mm)	1130
Înălțime (mm)	850
Adâncime (mm)	320
Număr de uși	2
Încuietoare	Swinghandle, prepared for Half cylinder

Tabel articole

Descriere	Greutate cupru (kg/km)	Cod comandă
Cable management enclosure Series J, 2 doors, size 2 dotted surface, H=850 W=1130 D=320mm, door opening angle 180°		IG009505
Accesorii opționale		
Mountingplate for IG009505, H=735 W=1035 D=6mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009555
plastic base frame sizes 2/S6 1200/400 plastic base frame serving as a foundation for plinth		IG790330
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 2/S6/310 (absorption mat)		IG793820
Plinth Polyester Series J size 2, RAL7035 H=905 W=1110 D=310mm		IG009315
Ground plate for Wall mounting for IG009305 H=285 W=1085 D=4mm		IG009325
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009405 & IG009505 H=288 W=1088 D=4mm		IG009425

Tabel articole

Descriere	Greutate cupru (kg/km)	Cod comandă
Accesorii opționale		
Copper busbar Set 4-pole, 30x10mm for Size 2 For IG009405 and IG009505, 10 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	9610	IG0090312
Copper busbar, 30x10mm for Size 2 For IG009405 and IG009505, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	2810	IG009P312
Obturator de 100 mm pentru sistem de bară de 185 mm Se montează pe piulițele prelungite M12		ISA05360
Insert (butuc) semi-cilindric cu 3 chei H36000, L=40 mm		IL900381