

Date tehnice pentru produs: IL312212-F

# Flush-mounted frame flat + door 2-12, 3-part system, 100mm

1 mm powder coated sheet steel, RAL9016, H=640 W=590 D=100mm



## SCHRACK-Info

- Modular designed flush-mounted frame with door
- Material: 1 mm powder coated sheet steel
- Available in sizes from 2U/12 to 3U/24 Modul-high enclosures
- When used with 3-part system wall box IL367xxx-F 100mm deep
- Standard version of door with flush plastic thumbturn operated via integrated double-bit lock
- Protection class: I
- Degree of protection: IP20C
- Impact resistance: IK08
- Color: RAL9016 (Traffic white)



## Fișe tehnice

|                    |        |
|--------------------|--------|
| Lățime netă (mm)   | 590,00 |
| Înălțime (mm)      | 640,00 |
| Adâncime netă (mm) | 100,00 |

## Fișe tehnice - Continuare

|                                            |                          |
|--------------------------------------------|--------------------------|
| Masă netă (kg.)                            | 7,00                     |
| COD EAN                                    | 9004840597509            |
| disipare (W)                               | -122,00                  |
| Temperatura minimă a mediului ambiant (°C) | -5                       |
| Temperatura maximă a mediului ambiant (°C) | 40                       |
| Categorie produs                           | Unterputz Flachverteiler |
| Culoare                                    | RAL 9016                 |
| Lățime panou contor                        | 2                        |
| UV                                         | 12                       |
| grad de protecție                          | IP20C                    |
| Descriere de bază                          | Ramă                     |

## Tabel articole

| Descriere                                                                                                                  | Cod comandă |
|----------------------------------------------------------------------------------------------------------------------------|-------------|
| Flush-mounted frame flat + door 2-12, 3-part system, 100mm<br>1 mm powder coated sheet steel, RAL9016, H=640 W=590 D=100mm | IL312212-F  |
| <b>Accesorii opționale</b>                                                                                                 |             |
| Wall box 2-12 flat, 3-part system 100mm deep, 84MW<br>1 mm galvanised sheet steel, H=635 W=580 D=100mm                     | IL367212-F  |
| Modular chassis 2-12K flat, 4-rows, depth 100 mm<br>Front plates sheet steel, complete                                     | IL148912-A  |