

Date tehnice pentru produs: IL312312-F

Flush-mounted frame flat + door 3-12, 3-part system, 100mm

1 mm powder coated sheet steel, RAL9016, H=640 W=810 D=100mm



SCHRACK-Info

- Modular designed flush-mounted frame with door
- Material: 1 mm powder coated sheet steel
- Available in sizes from 2U/12 to 3U/24 Modul-high enclosures
- When used with 3-part system wall box IL367xxx-F 100mm deep
- Standard version of door with flush plastic thumbturn operated via integrated double-bit lock
- Protection class: I
- Degree of protection: IP20C
- Impact resistance: IK08
- Color: RAL9016 (Traffic white)



Fișe tehnice

Lățime netă (mm)	810,00
Înălțime (mm)	640,00
Adâncime netă (mm)	100,00

Fișe tehnice - Continuare

Masă netă (kg.)	5,60
COD EAN	9004840597585
disipare (W)	-163,00
Temperatura minimă a mediului ambiant (°C)	-5
Temperatura maximă a mediului ambiant (°C)	40
Categorie produs	Unterputz Flachverteiler
Culoare	RAL 9016
Lățime panou contor	3
UV	12
grad de protecție	IP20C
Descriere de bază	Ramă

Tabel articole

Descriere	Cod comandă
Flush-mounted frame flat + door 3-12, 3-part system, 100mm 1 mm powder coated sheet steel, RAL9016, H=640 W=810 D=100mm	IL312312-F
Accesorii opționale	
Wall box 3-12 flat, 3-part system 100mm deep, 132MW 1 mm galvanised sheet steel, H=635 W=800 D=100mm	IL367312-F
Modular chassis 3-12K flat, 4-rows, depth 100 mm Front plates sheet steel, complete	IL148812-A