


Date tehnice pentru produs: IL901820--

Meter Connection Terminal 50A for Czech Republic, wired 1,8m

Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm², flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019



SCHRACK-Info

- Meter Connection Terminal 3-pol+2N With TRE 50A, for EVU Czech Republic, Vienna, Tyrol and Styria
- It makes it possible to replace devices without interrupting the power supply
- Power loss 3,3W at 50A over all three phases
- 400VAC, 50Hz
- Material Terminal Inserts from Silver-Plated Copper
- OVE Zertifiziert, RoHS konform, OVE R21:2019
- Ambient Temperature max. 60°C
- Conductor Material/Type Copper 2,5-16mm², rigid, solid and stranded /flexible with crimped ferrule, insertion depth of conductor 18-22mm
- Meter pins IL900190
- Tightening torque of Conductor max. 3Nm

Fișe tehnice

Fișe tehnice - Continuare

Lățime netă (mm)	330,00
Înălțime (mm)	250,00
Adâncime netă (mm)	35,00
Masă netă (kg.)	1,62
COD EAN	9004840985054
disipare (W)	78,00
Temperatura minimă a mediului ambiant (°C)	0
Temperatura maximă a mediului ambiant (°C)	60

Descriere	Cod comandă
Meter Connection Terminal 50A for Czech Republic, wired 1,8m Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm ² , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019	IL901820