

Date tehnice pentru produs: ILT40800-A

Celulă pentru plecări NH, 1042mm, 800A, 50x10 cupru



SCHRACK-Info

- **General** : Type-tested Modul 2000TT outgoing fields for HRC in-line fuse switches up to 630A
- **Material** :
 - Corpus: 1.5mm galvanised sheet steel
 - Doors: Single door and double door: 1.5mm sheet steel
- **Door** :
 - Made of sheet steel and equipped with M8 threaded bolts for earthing. Enclosures in widths 602mm and 822mm are single door versions, enclosures in widths 1042mm and 1242mm are double door versions
 - On single door enclosures, the door is mounted on three double-sided hinges for right-hand opening (=hinged right). On double door enclosures, hinges are not reversible, the left door wing is locked separately with an inner three-point lock
- **Lock** : Three-point rod lock with swing handle (without lock insert), does not slide inward. The standard lock can be exchanged for profile half cylinders (DIN cylinders) from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Roof** :
 - Two cut-outs for cable entries at widths 602mm and 822mm, three cut-outs at width 1042mm and four cut-outs at width 1242mm
 - Gland plates from our accessories are required for completion
- **Side cut-out** : Contacting possibility for the main busbar. 1 PU (=2 pieces) side covers **IL920001** per enclosure is necessary
- **Baying kit** : A baying kit for baying a second Modul 2000TT enclosure is included
- **Plinth** : 100mm high with cable entry options on the sides. Optionally it is possible to stack two 100mm high plinths on top of each other

- **Protection class** : I
- **Degree of protection** : Standard IP31 up to 1250A, without door it's possible up to 1600A, with corresponding components from our accessories (exhaust filter, gland plates and plinths) IP54 is possible up to 1250A
- **Impact resistance** : IK10
- **Finish** : Textured powder coating
- **Color** : RAL 7035 (Light grey)
- **Delivery includes** :
 - Enclosure with plinth
 - Door with earthing studs
 - Main busbar system
 - Transparent polycarbonate covers
 - Transport connection for main busbar system
 - Baying kit for one more enclosure

Delivered on an Euro-pallet



Fișe tehnice

Lățime netă (mm)	1.042,00
Înălțime (mm)	2.140,00
Adâncime netă (mm)	400,00
Masă netă (kg.)	220,00
Temperatura minimă a mediului ambiant (°C)	-5
Temperatura maximă a mediului ambiant (°C)	40
grad de protecție	IP31
Material	tablă de oțel
Culoare	RAL7035
Lățime (mm)	1042
Înălțime (mm)	2138
Adâncime (mm)	400
disipare (W)	-1009,00
LxÎxA mm	1042x2140x400
COD EAN	9004840837261

Descriere	Greutate cupru (kg/km)	Cod comandă
Celulă pentru plecări NH, 1042mm, 800A, 50x10 cupru		ILT40800-A

Accesorii necesare

Tabel articole

Descriere	Greutate cupru (kg/km)	Cod comandă
Accesorii necesare		
Plăci laterale pentru Modul 2000TT (2 buc.)		IL920001
Cable entry gland plate (blind), IP66		IL958001-A
Cable entry gland plate, IP55, 9xØ3-20, 1xØ3-40, 2xØ3-70mm		IL958007-A
Cable entry gland plate, 4xM16, 6xM25/16, 8xM32/20		IL958002-A
Cable entry gland plate 2xM20, 8xM25/16, 4xM32/20, 1xM50/32 IP66		IL958003-A
Cable entry gland plate 2xM16, 12xM20, 2xM40/25, 2xM50/32 IP66		IL958004-A
Cable entry gland plate, IP66, 24xM16, 13xM20		IL958005-A
Cable entry gland plate, IP55, 44xØ3-14, 3xØ3-21, 2xØ3-30mm foam-elastic		IL958006-A
Accesorii opționale		
Set plăci frontale 4-42K complet, tablă de oțel, NH pentru suportji fuzibile NH		ILTAK442
Separator vert. pt. fuz. NH, măr. 00, sistem bare de 100mm	420	ISA05261
Adaptor dublu pt. separator vert. măr.00 pe sistem de 185mm	469	ISA05326
Mască de egalizare înălțimi, pt. sep. vert. măr. 00 (2 buc.) aliniază capacele la mărimile 1-3		ISA05329
Separator vert. pt. fuz. NH, măr. 1 pt. sistem bare de 185mm	1943	ISA05305
Separator vert. pt. fuz. NH, măr.2 pt. sistem bare de 185mm NH-Leiste	1952	ISA05311
Separator vert. pt. fuz. NH, măr. 3 pt. sistem bare de 185mm NH-Leiste	2662	ISA05320
Separator vert.pt. fuz.NH, sistem 185, măr.1 cleme V direct NH-Leiste, 3-polig	1965	ISA05306
Separator vert.pt. fuz.NH, sistem 185, măr.2 cleme V direct Portfuzibili NH cu cleme V	1965	ISA05312
Separator vert.pt. fuz.NH, sistem 185, măr.3 cleme V direct NH-Leiste, 3-polig	2685	ISA05321
Separator vertical ARROWII, Gr.00, 3 poli, 100mm, M8 Versiunea pentru integrarea transformatoarelor de curent	391	ISA05340
Separator vertical ARROWII, Gr.1, 3 poli, 185mm, M12 Versiunea pentru integrarea transformatoarelor de curent	1948	ISA05341
Separator mărime 2, 3-poli, M12, pt. trafo de crt. Versiunea pentru integrarea transformatoarelor de curent	1948	ISA05342
Separator mărime 3, 3-poli, M12, pt. trafo de crt. Versiunea pentru integrarea transformatoarelor de curent	2633	ISA05343

Tabel articole

Descriere	Greutate cupru (kg/km)	Cod comandă
Accesorii opționale		
Capac de protecție borne pt separatoare vert. măr. 1-3		ISA05334
Capac obturator 50 mm pentru separatoare verticale rezervă permite astuparea decupajelor prefabricate pentru separatoarele verticale NH		ISA05356
Capac obturator 100 mm pentru separatoare verticale rezervă permite astuparea decupajelor prefabricate pentru separatoarele verticale NH		ISA05357
Insert (butuc) semi-cilindric pt cheie doi pini 5mm, L=40mm		IU001906
Filtru de ieșire 252x252x38mm, IP54		IUKNE450
Segment frontal soclu 4A ventilat		IL957400
Side panels 400mm (1 pair) ventilated inklusive Schrauben, Ausschnitt 290x50mm		IL090140
Placă frontală 4B18, tablă de oțel cu decupare pentru suport fuzibile NH		ILT56418-A
Suport documentație, autoadeziv, A4		ASDRA400
Urechi de ridicare M12 pt. dulapuri AC și KC 1 Set=4 piese		ACLE9301
Mască plombabilă		IL900112-F