

Date tehnice pentru produs: LID13987--

Sutil Round2 LED 30W, 4000K, 2100lm, 120°, IP40, alb **€CONOMY**

complete with driver; 06 DOWNLIGHT FIX LED



Detalii produs

30W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 700mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.




Fișe tehnice

Lumeni (lm)	2100
Culoare lumină	alb rece
Temperatura culorii (K)	4000
Indice redare culoare	≥80
Durată de viață	30.000h
Dimabil	nu
Clasă de protecție	II
grad de protecție	IP40
Tip iluminare	LED Panel
Surse de lumină incluse	da

Fișe tehnice - Continuare

Număr lămpi	1
Dulie lampă	LED Platine
Unghiul de radiație (°)	120
Eficiență sistem (lm/W)	70
Factor de putere	0,9
Putere (W)	30
Balast	LED driver
Tensiune de alimentare AC (V)	220-240
Frecvență (Hz)	50/60
Montaj	Montaj încadrat în plafon
Decupaj mm (mm)	Ø 285
Adâncime montaj (mm)	50
Culoare	Alb
Material	plastic acril Die-cast aluminum
Înălțime (mm)	22
Diametru (mm)	295
Accesorii opționale	LID16598--
ØxH mm	295x22
DECUPAJ mm	Ø 285

Desen dimensional: Sutil Round2 LED 30W, 4000K, 2100lm, 120°, IP40, alb



Tabel articole

Descriere	Cod comandă
Sutil Round2 LED 30W, 4000K, 2100lm, 120°, IP40, alb complete with driver; 06 DOWNLIGHT FIX LED	LID13987
Accesorii opționale	
LED driver 230V 8-50W 180mA dimabil IP20 230V; 23 DRIVERS	LID16598