

Date tehnice pentru produs: QLIES0620-

Switch 4xRJ45 (PoE+) + 1RJ45 + 1xSFP, 126W, pentru șină DIN

4 x 10/100/1000Base-T PoE+ (802.3at) ports, 1 x RJ45Gigabit Combo + 1 Gigabit SFP(100/1G) slot, 1 x Terminal Block, input voltage 12VDC-55VDC, without power supply



SCHRACK-Info

The QLIES0620- Industry Ethernet Switch provides 4 PoE ports 10/100/1000 Base plus 2 port Gigabit SFP to enable high speed network at mission-critical environment.

With the industrial standard DIN-rail mount: this switch can be easily installed in the cabinet, plus the clearly visible status LEDs provide simple monitoring of port link activity.

Moreover, the SFP slots support pluggable modules that enabling you to choose from a variety of transceivers. This switch is Power Sourcing Equipment (PSE), and it is fully complied with IEEE 802.3at PoE standard at maximum 30W power budget per port. It helps to save infrastructure wiring costs dramatically by eliminating electric wiring and less UPS needed. Also, it is compatible with IEEE802.3af standard PD devices.

Key-Features

- 4 x 10/100/1000Base-T PoE ports
- 1 Gigabit Combo + 1 Gigabit SFP (100/1G) slot
- PoE ports can support the IEEE 802.3at standard and power up 30W
- 1000 Mbps-Full-duplex, 10/100Mbps-Full/Half-duplex
- Auto-Negotiation, Auto-MDI/MDIX
- -40°C to 75°C (-40°F to 167°F) operating temperature range
- DIN-Rail mount installation
- Metal case design and compliant with IP30 standard

- Wide input power range from 12 to 55 VDC

TECHNICAL DATA

- Standards & Protocols:
 - IEEE 802.3 10-BASE-T, Ethernet
 - IEEE 802.3u 100-BASE-TX, Fast Ethernet
 - IEEE 802.3ab 1000Base-T Gigabit Ethernet
 - IEEE 802.3z 1000Base-X Gigabit Ethernet
 - IEEE802.3x Flow Control and Back Pressure
 - IEEE 802.3af Power over Ethernet (PoE)
 - IEEE 802.3at Power over Ethernet Plus (PoE+)
- Buffer memory:
 - 1024KB
- Plug:
 - 4 x 10/100/1000Mbps PoE RJ45 port
 - 1 x Gigabit Combo (RJ45 / SFP)
 - 1 x 100/1000Base-X SFP Slot
 - 1 x Terminal Block
- Button:
 - DIP1 On: Port 5 supports TX Copper
 - DIP1 Off: Port 5 supports SFP (Default)
 - DIP2: Reserved
- Indicator:
 - PW1 (Power 1): Green / PW2 (Power 2): Green / ERR (Fault): Amber
 - LNK (RJ45): Green
 - SPD: Amber (1000) / Green (100) / Off (10)
 - SFP: Green (Link / Active)
- Transmission method:
 - Store-and-Forward
- Power consumption:
 - 12-55 (12/24/48) VDC Dual power input capable (Redundancy)
- Power:
 - Alarm Relay Output 1A @ 24VDC
- Energy consumption:
 - 6 watts (with no PoE PD attached)
 - 160 watts (with full PoE PD attached)
- Backplane:
 - 12Gbps
- MAC-Address Table:
 - 1K

- Data Rate:
 - 10/100/1000Mbps

Features

- PoE:
 - Power Budget: Max. 126Watts at 24 VDC and 48VDC power input
 - At 75°C - Maximum total power 65W at 12VDC power input
 - At 70°C - Maximum total power 36W at 12/24/48VDC power input
 - PD classification identity
 - PoE over current protection
 - PoE circuit sorting protection
 - PoE Power Output: Max. 15.4 watts (802.3af) or 36 watts (802.3at)
 - Power Pin Assignment: 1/2(+). 3/6(-)
- Security:
 - Protection:
 - Polarity Reversal
 - Overload Current

Performance

- Forwarding rate:
 - 1000Mbps port - 1,488,000pps
 - 100Mbps port - 148,000pps
 - 10Mbps port - 14,880pps
- Jumbo-Frames:
 - 10 K

Environment

- Temperature:
 - Operating: -40°C ~ 75°C
 - Storage: -40°C ~ 85°C
- Humidity (non-condensing):
 - Storage: 5% ~ 95%
 - Operating: 5% ~ 95%
- Application:
 - Desk, wall and chassis mounted

Physical Specifications

- Dimensions (W x D x H):
 - 40 x 105 x 38 mm
- Weight:
 - 720g

Reliability

- MTBF:
 - 5,510,304 hrs

Approval and Compliance

- Certification:
 - FCC Part 15 Subpart B Class A
 - CE
 - VCCI
- Security:
 - EN60950-1
- Housing:
 - EN61000-4-2 (ESD) Level 3
 - EN61000-4-3 (RS) Level 3
 - EN61000-4-4 (EFT) Level 3
 - EN61000-4-5 (Surge) Level 3
 - EN61000-4-6 (CS) Level 3
 - EN61000-4-8 (Magnetic Field) Level 3
 - UL508 (Pending)
 - EN 50121-4 (Pending)
 - IEC 60068-2-27
 - IEC 60068-2-32
 - IEC 60068-2-6
 - UL 508

Order Information

- QLIES0620-

Package Contents

- QLIES0620-
- Quick Installation Guide

Fișe tehnice

Lățime netă (mm)	40,00
Înălțime (mm)	38,00
Adâncime netă (mm)	105,00
COD EAN	4015867188514
Temperatura minimă a mediului ambiant (°C)	0
Temperatura maximă a mediului ambiant (°C)	70
Produs	Ethernet Switch
Viteză	10/100/1000Mbps
Porturi	6
Montaj	Șină DIN

Tabel articole

Descriere	Cod comandă
Switch 4xRJ45 (PoE+) + 1RJ45 + 1xSFP, 126W, pentru șină DIN 4 x 10/100/1000Base-T PoE+ (802.3at) ports, 1 x RJ45Gigabit Combo + 1 Gigabit SFP(100/1G) slot, 1 x Terminal Block, input QUES0620 voltage 12VDC-55VDC, without power supply	
Accesorii opționale	
Patchpanel TOOLLESS LINE, neechipat, 1 modul, montaj pe șină	HSEH010GS
Modul FO SFP 1000BaseSX LC Multimode VCSEL 850nm, 550m Pentru seria QL..	QLSFP3001
Modul FO SFP 1000BaseLX LC Singlemode 1310nm, 10km Pentru seria QL..	QLSFP3211
Sursă de alimentare industrială, 48VDC, 120W, șină DIN PoE Ready	QLPOW4840
Sursă de alimentare industrială, 48VDC, 480W, șină DIN PoE Ready	QLPOW4860
Sursă de alimentare, 110V-240VAC 50/60Hz; 48VDC/1.35A, 64,8W	QLPOW4801
Splicebox FO pt. șină DIN, 4 Fibre, LC, 50/125μm OM3 inclusiv pigtailuri și cupluri	HSELS043LR
Splicebox FO pt. șină DIN, 4 Fibre, LC, 9/125μm OS2 inclusiv pigtailuri și cupluri	HSELS049LR
Splicebox FO pt. șină DIN, 4 Fibre, LC, 50/125μm OM4 inclusiv pigtailuri și cupluri	HSELS044LR