

Date tehnice pentru produs: QLPOI3000-

Injector PoE+ (802.3at), Gigabit, Sursă de alim.internă, 30W

1 x 10/100/1000Base-T RJ45 Input Port, 1 x 10/100/1000Base-T RJ45 PoE Output Port



SCHRACK-Info

Advanced PoE SolutionThe LevelOne POI-3000 is a single-port, high-power PoE injector (PSE) for Remote PoE PD devices. The POI-3000 delivers up to 30W of PoE for current components such as wireless Access Points, pan-tilt-zoom (PTZ) IP cameras and video phones.

The injector is compatible with IEEE 802.3at PoE standard and backward compatible with IEEE 802.3af.

It can be used with 10/100Base-T network devices and the latest 1000Base-T devices such as Wi-MAX and wireless IEEE 802.11n access points.

The POI-3000 is equipped with many features so that users can benefit from flexible network installations with lower costs and less downtime.

The injector also supports high bandwidth for the network.

Key-Features

- Up to 30W PoE power
- Compliant with 802.3at standard
- Backward compatible with IEEE 802.3af
- Compatible with IEEE 802.3af or PoE legacy applications
- Safe for low power devices, they receive only the power they need
- Safe and reliable power supply for WLAN access points
- Automatic detection and protection of non-standard
- Ethernet ports
- Supports 10/100/1000Base-T LAN applications

- Unique locking feature for easy installation

TECHNICAL DATA

- Standards & Protocols:
 - IEEE 802.3 10Base-T, Ethernet
 - IEEE 802.3u 100Base-TX, Fast Ethernet
 - IEEE 802.3ab 1000Base-T, Gigabit Ethernet
 - IEEE 802.3af Power over Ethernet (PoE)
 - IEEE 802.3at Power over Ethernet Plus (PoE+)
- Plug:
 - 1 x 10/100/1000Base-T RJ-45 Input Port
 - 1 x 10/100/1000Base-T RJ-45 PoE Output Port
- Indicator:
 - Power, PoE
- Pin assignment and polarity:
 - 1/2(+), 3/6 (-)
- Power consumption:
 - 100-240V AC, 50/60Hz, 0.8A
- Power:
 - PoE DC 52V / 0.6A (30W)
- Energy consumption:
 - 30W (Max.)

Features

- PoE:
 - IEEE 802.3af/at compliant

Environment

- Temperature:
 - Operating: 0°C ~ 45°C
 - Storage: 0°C ~ 70°C
- Humidity (non-condensing):
 - Storage: 5% ~ 95%
 - Operating: 5% ~ 95%
- Mount:
 - Wall mount

Physical Data

- Dimensions (W x D x H):
 - 87.9 x 51.3 x 166 mm
- Weight:
 - 350g

Reliability

- MTBF:
 - 87.0966(K.hrs)

Approval and Compliance

- Certification:
 - FCC Part 15, CE, RoHS
- Security:
 - EN 60950:2006

Order Information

- QLPOI3000-

Package Contents

- QLPOI3000-

Fișe tehnice

COD EAN	4015867158111
Temperatura minimă a mediului ambiant (°C)	0
Temperatura maximă a mediului ambiant (°C)	70
Viteză	10/100/1000Mbps
Masă netă (kg.)	0,35
PREȚ	568,60

Descriere	Cod comandă
Injector PoE+ (802.3at), Gigabit, Sursă de alim.internă, 30W 1 x 10/100/1000Base-T RJ45 Input Port, 1 x 10/100/1000Base-T RJ45 PoE Output Port	QLPOI3000