

Date tehnice pentru produs: SR3PDIEM10

PDU Essential Metered; 24xC13; 6xSchuko; 400V; 32A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 32A/400V | 22kW
- Output: 24xC13 0° IEC Socket 6xCEE7/3 35° Socket
- 6xMiniature Circuit Breaker C16A
- split into three phases, each phase split into two blocks, each block fused with a MCB
- Supply cable: 3.0m | 4mm²
- with CEE 32A plug, red
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Fișe tehnice

Lungime (mm)	1.786,08
Lățime netă (mm)	45,00
Înălțime (mm)	94,00
Masă netă (kg.)	5,50
COD EAN	4057298233128
PREȚ	8.850,00
Temperatura minimă a mediului ambiant (°C)	-5
Temperatura maximă a mediului ambiant (°C)	45
Tensiune nominală	400V
grad de protecție	IP20
Tipul produsului	Metered Essential
Număr de prize	30
Tip bucsă	24 x IEC320 C13 und 6 x CEE7/3
Curent nominal (A)	32
Phases per feed	3
Tip conexiune	CEE 16A roșu
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Montaj	Bracket (L-shape)

Descriere	Cod comandă
PDU Essential Metered; 24xC13; 6xSchuko; 400V; 32A	SR3PDIEM10
Measurement per phase, incl. mounting bracket with screws	