

Date tehnice pentru produs: SR3PDIPM09

PDU PRO Metered, 36xC13, 6xC19, 400V, 32A

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 36x C13 IEC Socket + 6 x C19 IEC Socket
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

- Packed in cardboard box
- Length 2075 mm

Fișe tehnice

Lungime (mm)	2.075,00
Lățime netă (mm)	56,00
Înălțime (mm)	65,00
Masă netă (kg.)	6,77
COD EAN	4057298207938
PREȚ	16.100,00
Temperatura minimă a mediului ambiant (°C)	0
Temperatura maximă a mediului ambiant (°C)	50
Tensiune nominală	400V
grad de protecție	IP20
Tipul produsului	Metered
Număr de prize	42
Tip bucsă	36 x IEC320 C13 und 6 x IEC320 C19
Curent nominal (A)	32
Phases per feed	3
Tip conexiune	CEE 32A roșu
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montaj	Bracket (L-shape)

Descriere

Cod comandă

PDU PRO Metered, 36xC13, 6xC19, 400V, 32A

SR3PDIPM09

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!