

Date tehnice pentru produs: SR3PDIPP02

PDU PRO Metered+, 36xCombo Outlets (C13, C15, C19, C21), 400V, 16A

Metering per outlet, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 36x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </I

Fișe tehnice

Lungime (mm)	1.568,70
Lățime netă (mm)	56,00
Înălțime (mm)	71,00
COD EAN	4057298230318
PREȚ	23.110,00
Temperatura minimă a mediului ambiant (°C)	0
Temperatura maximă a mediului ambiant (°C)	50
Tensiune nominală	400V
grad de protecție	IP20
Tipul produsului	Metered+
Număr de prize	36
Tip bucsă	36 x Combo Socket (C13/C15/C19/C21)
Curent nominal (A)	16
Phases per feed	3
Tip conexiune	CEE 16A roșu
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montaj	Bracket (L-shape)

Descriere	Cod comandă
PDU PRO Metered+, 36xCombo Outlets (C13,C15,C19,C21), 400V, 16A Metering per outlet, incl. mounting bracket with screws	SR3PDIPP02